






ID-11 Plus

VDC
12~24

ID-11RS


FS-14P



Dual Controller Capability



CONTROLLER SERIES



Features

- 3 Slots of 10 Amp High Power Output
- 3 Slots of Combined 10 Amp High Power Output
- 5 Slots of 0.2 Amp Output For Signaling
- 1 Slots of Common Positive (0.2Amp) And Negative Output
- 11 Programmable Button
- Multiple Features Include Interlock Function
- Fleet Sync Function For Quick Setup
- Ability To Sync With A Second Controller

ID-11

VDC
12-24



Controller

- 11 Independent keys with backlight for indication
- Flash pattern indicator
- Momentary switch setting
- Warning/traffic light flash pattern indicator
- For use with positive trigger devices only

Product Code	ID-11
Voltage	12V-24V
Dimension	ID-11RS(Controller): 100mm x 60mm x 18.5mm

Specification

Product Code	ID-11 Plus
Approval	R10
Working Temperature	-30°C~+70°C
Input Voltage	12-24 VDC
Input I/O	Panel x2 Power x1
Output Voltage	same as input voltage
Output I/O	10 amp at 12VDC / 5 amp at 24VDC x3 10 amp at 12VDC / 5 amp at 24VDC (Shared) x 3 0.2 amp x5 Positive / Negative Common Trigger at 0.2 amp (2 slot) x1
Dimension	ID-11RS (Controller): 100mm x 60mm x 18.5mm FS-14P (Fuse Box): 148mm x 92mm x 25mm